Advanced Monolithic Systems

AMS3100A-2.5

MICROPOWER VOLTAGE REFERENCE

FEATURES

- **±12 mV (±0.5%) max. initial tolerance (A grade)**
- **Operating Current 20µA to 20mA**
- **Low Voltage Reference 2.50V**
- **Max. 0.5Ω Dynamic Impedance (A grade)**
- **Low Temperature Coefficient**
- **SOT-23 Package Available**
- **±5% Output Voltage Precission Trimming**
- **Low cost**

APPLICATIONS

- **Battery Powered Systems**
- **Instrumentation**
- **A/D, D/A Converters**
- **Temperature measurement**
- **Current sources**
- **Notebook/Personal Computer**
- **Monitors/ VCR/ TV**
- **Pagers**

GENERAL DESCRIPTION

The AMS3100A-2.5 are two-terminal micropower band-gap voltage reference that feature a very low dynamic impedance and good temperature coefficient, operating over a 20µA to 20mA current range. AMS3100A-2.5 is trimmed at wafer test level to optimize the temperature coefficient and tight output voltage tolerance. The advanced process technology used, makes the AMS3100A-2.5 exceptionally tolerant of capacitive loading, making it easy to use in almost any reference application. The wide dynamic operating range allows its use with widely varying supplies with excellent regulation. The extremely low power drain, makes these reference diodes useful for micropower circuitry. These voltage references can be used to make portable meters, regulators or general purpose analog circuitry with battery life approaching shelf life. Further more, the wide operating current allows it to replace older references with a tight tolerance part. A third terminal allows the reference voltage to be adjusted to ±5% to calibrate out system errors.

The AMS3100A-2.5 is operating over a -40°C to 85°C temperature range and is available in the space saving SOT-23 package.

ORDERING INFORMATION:

TOL.	PACKAGE TYPE	OPERATING TEMPERATURE RANGE
	SOT-23	
±12mV	AMS3100A-2.5AM	-40°C to 85°C
±25mV	AMS3100A-2.5BM	-40°C to 85°C
±25mV	AMS3100A-2.5CM	-40°C to 85°C

PIN CONNECTIONS

3L SOT-23
(M)



A = Adjust pin.

Top View

http://www.BDTIC.com/AMS

ABSOLUTE MAXIMUM RATINGS

Reverse Current	30mA	Lead Temperature	
Forward Current	10mA	Vapor phase (60 sec)	215°C
Operating Temperature Range	-40°C to 85°C	Infrared (15 sec.)	220°C
Storage temperature	-55°C to +150°C	Thermal Resistance (θ_{JA})	410°C/W

ELECTRICAL CHARACTERISTICS

Electrical Characteristics at I_R = 100 µA, and T_A = +25°C unless otherwise specified.

Parameter	Conditions	AMS3100A-2.5			AMS3100B-2.5			AMS3100C-2.5			Units
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
Reverse Breakdown Voltage (Note 3)	I_R - 100 µA	2.488	2.500	2.512	2.475	2.500	2.525	2.450	2.500	2.550	V
Reverse Dynamic Impedance (Note 3)	I_R - 100 µA, f =20Hz		0.2	0.60		1			1		Ω
Reverse Breakdown Voltage Change with current (Note 3)	10µA ≤I_R ≤1mA 1mA ≤I_R ≤20mA		1.0 10				1.0 10			2.0 20	mV
Min. Operating Current (Note 3)			12	20 **25**		13	20 **30**		13	20 **30**	µA µA
Wide Band Noise (Note 4)	I_R - 100 µA, 10Hz ≤ f ≤ 10kHz		120			120			120		µV
Temperature Coeff. (Note 5)			**25**			**50**			**100**	**150**	ppm/°C
Long Term Stability (Note 4)	T_A=25°C±.1°C T = 1000 Hr		20			20			20		ppm

Note 1: Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is intended to be functional, but do not guarantee specific performance limits. For guaranteed specifications and test conditions, see the Electrical Characteristics. The guaranteed specifications apply only for the test conditions listed.

Note 2: Parameters identified with **boldface type** apply at temperature extremes. All other numbers apply at $T_A = T_J$ = 25°C.

Note 3: Guaranteed and 100% production tested

Note 4:. Guaranteed but not 100% production tested. These limits are not used to calculate average outgoing quality levels.

Note 5: The average temperature coefficient is defined as the maximum deviation of reference voltage at all measured temperatures between the operating T_{MAX} and T_{MIN}, divided by T_{MAX} - T_{MIN}. The measured temperatures are -40°C, 25°C and 85°C.

TYPICAL APPLICATIONS

2.5V Reference



Wide Supply Range, Adjustable Reference



*Does not affect Temperature Coefficient

http://www.BDTIC.com/AMS

TYPICAL PERFORMANCE CHARACTERISTICS

Reverse Characteristics



Reverse Characteristics



Forward Characteristics



Reverse Dynamic Impedance



Temperature Drift



Reverse Dynamic Impedance



Filtered Output Noise



Noise Voltage



Response Time



http://www.BDTIC.com/AMS

PACKAGE DIMENSIONS inches (millimeters) unless otherwise noted.

3 LEAD SOT-23 PLASTIC PACKAGE (M)



http://www.BDTIC.com/AMS